

## Technical details MSMLS50-GL28

<b>Manufacturer</b>	ALU+ limited
<b>Type</b>	<ul style="list-style-type: none"> <li>• Glazed-in louvre, with a pitch of 50mm.</li> <li>• All profiles are formed from mild steel sheets</li> <li>• Available for glazing thickness 28mm.</li> <li>• Z-shaped louvre blades</li> </ul>
<b>Material</b>	<ul style="list-style-type: none"> <li>• Mild Steel - frame profile and blades.</li> <li>• Profile thickness: Blade - minimum 1.2mm. Frame – minimum 1.6mm</li> </ul> <p>Finishes :</p> <ul style="list-style-type: none"> <li>• Mill Finish</li> <li>• Polyester powder coated - BS6496</li> <li>• Powder coating in any RAL or B/S colour available</li> <li>• Thickness of powder coating 40-60µm</li> </ul> <p>Protection :</p> <ul style="list-style-type: none"> <li>• Steel Insect &amp; bird mesh screens tack welded to the rear of louvre as an e/o option</li> </ul>
<b>Manufacture</b>	<ul style="list-style-type: none"> <li>• The glazed-in louvre consists of a 25mm rebate, mitre cut at 45 degree angles and welded together.</li> <li>• The steel blades are then welded to the box frame.</li> <li>• The blade height is 61mm, &amp; the visual free area is 76%.</li> <li>• Depth to fit 41.2mm.</li> </ul>
<b>Assembly</b>	Custom made by our skilled Craftsmen to your exact requirements

